
Tel: 01246 296 930 • Fax: 01246 296 940 Email: fasteners@harrisonsilverdale.co.uk Internet: http://www.harrisonsilverdale.co.uk





Press In Stud for Thermoset

Part No.	Thread A	Ext. Diam. E	Length B	Stud length S	Hole Diam L	Min wall W
PIS020L	M2.0	3.35	4.00	6-16	3.1	1.6
PIS025L	M2.5	4.20	5.30	6-16	3.8	2.0
PIS030L	M3.0	4.20	5.30	6-16	3.8	2.0
PIS035L	M3.5	5.00	6.30	6-25	4.6	2.5
PIS040L	M4.0	5.80	7.40	6-25	5.4	2.5
PIS050L	M5.0	6.60	8.30	6-25	6.2	2.5
PIS060L	M6.0	8.20	9.20	6-25	7.8	2.8
PIS080L	M8.0	9.70	9.20	10-25	9.3	3.8

The PIS Pressin have the same features as the PI range but with a males thread. These inserts are designed to provide permanent, strong, thread forms in Thermoset and other hard plastics. The three bands of sharp helical knurling ensure the insert broaches its way into the plastic whilst the debris packs the relief to ensure the insert locks in place providing high resistance to torque loads and adequate resistance to pull out loads in these plastics. Material and Finish:-Brass Self ColourTo Specify Use: Series No / Part No / Length (eg 20104 PIS030HL12 M3x12)

All information is given for guidance only and designers should satisfy themselves as to the suitability of the specification by requesting samples