



## Flush Head Closed Rivet Nuts

Part No.	Thread M	Panel Size S	Body Diam. D	Head Dim. E	Head Diam. T	Length L	Hole size P	Dim. R
SB S3	M3	0.5 - 2.0	4.7	0.4	5.5	12.3	4.8	8.3
SB S3A	M3	0.5 - 2.0	5.0	0.4	5.8	11.7	5.1	7.7
SB 4	M4	0.5 - 2.0	6.3	0.4	7.0	14.0	6.4	9.8
SB 4A	M4	0.5 - 2.0	6.0	0.4	6.8	13.0	6.1	9.0
SB 5	M5	0.5 - 2.0	7.1	0.5	8.0	17.5	7.2	13.3
SB 5A	M5	0.5 - 2.0	7.0	0.5	8.0	16.7	7.1	12.7
SB 6	M6	1.0 - 3.0	9.4	0.6	10.4	20.0	9.5	15.0
SB 6A	M6	1.0 - 2.0	9.0	0.5	10.0	19.0	9.1	14.5
SB 8	M8	1.0 - 3.0	12.6	0.6	13.6	20.5	12.7	15.3
SB 8A	M8	1.0 - 3.0	10.5	0.6	11.3	21.5	10.6	16.0
SB 8B	M8	1.0 - 3.0	11.0	0.5	12.0	21.3	11.1	16.3
SB 10	M10	1.0 - 3.0	14.1	0.7	15.2	24.5	14.2	19.8
SB 10A	M10	1.0 - 3.5	13.0	0.7	14.4	25.3	13.1	21.0
SB 12	M12	1.4 - 4.0	16.1	0.7	17.2	25.5	16.2	21.0
SB 12A	M12	1.4 - 4.0	16.0	0.7	17.2	32.9	16.2	28.5

These rivet nuts are a high performance part for demanding applications. The SB range have a reduced countersunk head to allow almost flush fitting without the need for countersinking the hole. The closed end provides a sealed nut. They are machined from bar rather than forged and have a ribbed wall for maximum torque resistance.

Material: Mild Steel or 303 Stainless Steel (code SS)      Finish: Trivalent Zinc

**All information is given for guidance only and designers should satisfy themselves as to the suitability of the specification by requesting samples**