
Tel: 01246 296 930 • Fax: 01246 296 940 Email: fasteners@harrisonsilverdale.co.uk Internet: http://www.harrisonsilverdale.co.uk





Plas-Tight 45° Torx Pan Head

Part No.	Thread	D1	K	С	Recess	
20201 25**	2.5	4.00	1.60	2.55	1	
20201 30**	3	5.00	1.95	3.05	1	
20201 35**	3.5	6.00	2.30	3.55	1	
20201 40**	4	7.00	2.45	4.06	2	
20201 50**	5	8.00	2.80	5.06	2	

	Legend
*	Usually Available from Stock
**	Non-preferred (Possible Lead Times)
***	Special Order Only

Thread/Length	4	5	6	7	8	10	12	16	20	25	30	35
2.5	***	***	*	***	*	***	***	***	***	***	***	***
3	***	***	*	***	*	*	*	*	*	***	***	***
3.5	***	***	*	***	*	*	*	*	***	*	***	***
4	***	***	*	***	*	*	*	*	*	*	***	***
5	***	***	***	***	***	*	*	*	*	*	*	***

Plas-Tight 45° Screws are a Metric 3-Lobe Bodied Screw that encompass a 45º thread profile which allows deep thread penetration into the plastic material. The 3-lobe body allows displaced material to cold flow back into relief areas which minimises radial stress and reduces the possibility of failure.

Material: Steel, Stainless Steel A2 (Selected Sizes Only)

Finish: Zinc Plated, Self Colour

For the part number replace ** with the required length found in the tables below: